

HOLLOW METAL DOORS & FRAMES

DHHM-DF — Hollow Metal Door & Frame

DHHM-D — Hollow Metal Door

DHHM-F — Hollow Metal Frame

Gauge and Construction

- 18 gauge (standard)
- Optional gauges: 14, 16, and 20 gauge

Core Options

- Polystyrene core (standard)
- Optional cores: honeycomb, fiberboard, urethane

Steel Type and Coating Options

- Cold-rolled steel (standard)
- Optional materials/coatings:
 - A40 and A60 galvanized
 - G90 galvanized

Finish Options

- Gray primer (standard)
- Optional finishes: unprimed (galvanized), or factory prefinished in thousands of colors

Face Style and Cutout Options

- Flush face (standard)
- Available options: vision lite kits, louvers, panel designs, including wood-grain styles

Design and Reinforcement Features

- Exclusive door design includes: mechanically interlocking pan-and-lid construction
- Hinge reinforcement: 7-gauge hinge reinforcements, with an extra-long top hinge reinforcement (standard)

Hardware Prep and Fire Rating

- Closer reinforcement: standard (available with flush top)
- Fire rating: up to 3-hour fire rating available



Door Sizes

2'0 x 6'8	2'6 x 7'0
2'4 x 6'8	2'8 x 7'0
2'6 x 6'8	2'10 x 7'0
2'8 x 6'8	3'0 x 7'0
2'10 x 6'8	3'4 x 7'0
3'4 x 6'8	3'6 x 7'0
3'6 x 6'8	3'8 x 7.0
3'8 x 6'8	4'0 x 7'0
4'0 x 6'8	3'0 x 8'0
2'0 x 7'0	4'0 x 8'0
2'4 x 7'0	3'0 x 9'0

Frame Sizes

4 3/4"
5 3/4"
5 7/8"
6 3/4"
7 1/8"
7 3/4"
8 1/4"
8 3/4"

Throat size is 1" smaller than the frame size

Ordering Information

- Door size (W x H), hand, swing
- Gauge and core
- Steel/coating (CRS / A40/A60 / G90)
- Finish (primer / prefinished color)
- Cutouts (vision lite / louver)
- Fire rating requirement (if any)
- Frame throat size / wall condition