

MAGLOCKS



Specify When Ordering

- Configuration: Single / Double
- Holding force: 600 lb / 1,200 lb
- Sensor option: Standard (lock status) / DS (lock + door status)
- Voltage: 12 VDC / 24 VDC
- Finish: Anodized aluminum

Overview

UL-Listed maglocks provide a standards-compliant locking solution for retail, healthcare, banking, and other high-security facilities. They mount on hollow metal, wood, aluminum, glass, and composite doors.

Configurations

- Mounting: Surface mount
- Door types: Single or double
- Holding force: 600 lb or 1,200 lb models

Built-in functions (all models)

DS variants (door-status models)

- Add a door status sensor (reed) in addition to the lock status/LED

 <p>600 LB, SINGLE</p>	Holding Force	600 lb
	Input Voltage	12/24 VDC (UL-Listed power supply required)
	Current Draw	0.50 A @ 12 VDC; 0.25 A @ 24 VDC
	Dimensions	9.84 in (W) × 1.65 in (H) × 1.02 in (D)
	Housing	Anodized aluminum
	Relock Delay	0–90 s (adjustable)
	Sensor	Lock status (NO/NC) with visible LED
	Output Relay	Up to 1 A @ 24 VDC

 <p>600 LB, DOUBLE</p>	Holding Force	600 lb
	Input Voltage	12/24 VDC (UL-Listed power supply required)
	Current Draw	0.50 A @ 12 VDC; 0.25 A @ 24 VDC
	Dimensions	9.84 in (W) × 1.65 in (H) × 1.02 in (D)
	Housing	Anodized aluminum
	Relock Delay	0–90 s (adjustable)
	Sensor	Lock status (NO/NC) with visible LED
	Output Relay	Up to 1 A @ 24 VDC

MAGLOCKS

 <p>1200 LB, SINGLE</p>	Holding Force	1200 lb
	Input Voltage	12/24 VDC (UL-Listed power supply required)
	Current Draw	0.50 A @ 12 VDC; 0.30 A @ 24 VDC
	Dimensions	10.47 in (W) × 2.87 in (H) × 1.58 in (D)
	Housing	Anodized aluminum
	Relock Delay	0–90 s (adjustable)
	Sensor	Lock status (NO/NC) with visible LED
	Output Relay	Up to 1 A @ 24 VDC

 <p>1200 LB, DOUBLE</p>	Holding Force	1200 lb
	Input Voltage	12/24 VDC (UL-Listed power supply required)
	Current Draw	0.50 A @ 12 VDC; 0.60 A @ 24 VDC
	Dimensions	20.94 in (W) × 2.87 in (H) × 1.58 in (D)
	Housing	Anodized aluminum
	Relock Delay	0–90 s (adjustable)
	Sensor	Lock status (NO/NC) with visible LED
	Output Relay	Up to 1 A @ 24 VDC

ACCESSORIES



10LZBRMAG3UL
L & Z bracket
600 lb single



10LZBRMAG1UL
L & Z bracket
1200 lb single



10MAG6LZUL
(2) L & Z bracket
600 lb single



10MAG5LZUL
(2) L & Z bracket
1200 lb single



10UBRACKETUL
Glass door
mounting kit



10RIMHOUSING3UL
Armature plate
housing, 600 lb



10RIMHOUSING1L
Armature plate
housing, 1200 lb



10FILLER14UL
Filler plate,
0.25 × 0.75 in



10FILLER12UL
Filler plate,
0.50 × 0.75 in



10FILLER34UL
Filler plate,
0.75 × 0.75 in



10SPACER3UL
Vertical spacer
bracket, 600 lb



10SPACER1UL
Vertical spacer
bracket, 1200 lb